

CT - M 270 N

Engine data version 07.2017

| Basic Data | | |
|---|--------------------|----------------------------|
| Fuel | | natural gas |
| Minimum heating value Hu | kWh/m ³ | 10 |
| Methane number | Mz | ≥ 80 |
| Heating water system temperature | °C | 70 / 90 |
| CHP coefficient | | 0,65 |
| Frequency | Hz | 50 |
| Nominal voltage Un | V | 400 |
| Speed | min ⁻¹ | 1.500 |
| Intercooler version | °C | - |
| Electrical nominal power at cosφ=1 | kW | 264 |
| Thermal power utile * | kW | 409 |
| Fuel power input | kW | 740 |
| Efficiency electrical | % | 35,7 |
| Efficiency thermal | % | 55,3 |
| Efficiency total | % | 91,0 |
| After-treatment of exhaust gases | | lambda=1 and three-way-cat |
| Pollutant emissions (dry exhaust gas with 5% O ₂) | | |
| Formaldehyde (CH ₂ O) | mg/Nm ³ | < 20 |
| NOx measured as NO ₂ | mg/Nm ³ | < 250 |
| CO | mg/Nm ³ | < 250 |

| Engine | | |
|-----------------------------------|---------|-----------------|
| Engine Type | | MAN E 3262 E302 |
| Combustion type | | gas engine |
| Operating principle | | 4-stroke |
| Cylinder No./ configuration | | 6 in line |
| Displacement | l | 25,8 |
| Engine power according ISO 3046/1 | kW_mech | 275 |
| Specific fuel consumption | MJ/kWh | 9,69 |

| Generator | | |
|--|-----|----------------------|
| Type of Generator | | Leroy Somer 46.3 L11 |
| Apparent power | kVA | 365 |
| Voltage | V | 400 |
| Stator connection | | Y |
| Ambient temperature max. | °C | 40 |
| Protection class | | IP23 |
| Radio interference class acc. VDE 0875 | | N |
| Heating class | | H |

| Heat exchanger unit | | |
|---|----|-----|
| Engine cooling water heat output | kW | 245 |
| Intercooler HT heat output | kW | - |
| Intercooler LT heat output | kW | - |
| Exhaust heat (cooling up to 120°C) | kW | 164 |
| Total thermal power output via plate heat exchanger | kW | 409 |
| Heating water temp. inlet max. | °C | 70 |
| Heating water temp. outlet max. | °C | 90 |

| Design and operation | | |
|--|--------------------|-------|
| Lubricant oil content engine min./max. | l | 70/90 |
| Lubricant oil storage tank | l | |
| Generator efficiency cosφ=1, 400V | % | 96,0 |
| COGEN current rated | A | 476 |
| Radiation heat module | kW | 31 |
| Intake air mass flow | kg/h | 8.380 |
| Outlet air mass flow | kg/h | 7.484 |
| Combustion air mass flow at 25°C and 1013 mbar | kg/h | 896 |
| Intake air temp. ISO 3046 dimensioning | °C | 25 |
| Exhaust mass flow wet | kg/h | 972 |
| Exhaust volume flow, dry 0% O ₂ (0°C, 1013 mbar) | Nm ³ /h | 800 |
| Permissible exhaust gas back pressure downstream of module for piping | mBar | 5 |
| Externe Pressung des Lüfters | Pa | 107 |
| Airborne noise (sound pressure level) encaapsulated modul at 1 m distance ** | dB(A) | 75 |
| Exhaust noise (sound pressure level) with primary exhaust silencer at 1 m distance *** | dB(A) | 75 |

| Connections and interfaces | | |
|--|--|--------------|
| Gas inlet | | DN40 / PN16 |
| Exhaust gas outlet (flange) | | DN200 / PN10 |
| Condensate drain | | R 1/2" |
| Heating water inlet/outlet (flange) | | DN65 / PN16 |
| Intercooling system LT inlet/outlet (flange) | | - |
| Flanges conform to DIN EN 1092-1 | | |

| Module dimensions and weigh * | | |
|-------------------------------|----|-------|
| Length | mm | 4.102 |
| Width | mm | 1.819 |
| Height | mm | 2.191 |
| Operating weight approx. | kg | 5.000 |

* Possibility of increasing thermal power by using a calorific value waste-gas heat exchanger.

** Measurement of noise in free field, tolerance ± 1.0 dB(A)

*** Measurement of noise in free field, tolerance ± 2.5 dB(A)

* Dimensions with ventilator and feet. Length without stillage for return riser.

Tolerance for preceding heat output ±7% and energy input +5% according full duty.

All further data are valid for grid parallel operation. Derating through adjustment of reactive power factor cosφ by energy supplier possible.

Features of our scope of supply are only warranted, when SES expressly stated the warranty. Power and efficiencies according ISO 3046/1 and DIN 6271, at 25°C air temperature, 100 kPa air pressure (at 100 m above sea level), 30% rel. humidity, methane number see basic data, as well as cosφ= 1. As fuel natural gas according German DVGW Worksheet G260, category 2, group L/H is valid. Furthermore following documents are valid: MAN Operating Materials and Operating Instructions for MAN Industrial Gas Engines in latest edition. These documents are available on request. A gas flow pressure before module of 20 - 50 mbar is necessary (other gas flow pressures are available on request). A temperature of intake air of 10 °C to 25 °C has to be ensured. Data for other operating conditions or gas qualities are available on request.